

50 Ohm RF Coaxial Cables


ACCL (ALMR) 300

Construction


Inner conductor	Solid copper	Φ1.78 mm
Dielectric	Foam /Solid PE	Φ4.83 mm
Shield	Bonded aluminium foil	Φ4.98 mm
Outer conductor	Tinned copper braid	Φ5.72 mm
Sheath	PVC/PE	Φ7.62 mm

Electrical & Mechanical Characteristics

Impedance	50±3 Ohm
Nominal capacitance	78.8 pF/m
Velocity of propagation	85%
Insulation resistance	>5000 Mohm.Km
Inner conductor resistance	7.01 Ohm/Km
Outer conductor resistance	7.26 Ohm/Km
Operating temperature range	-40°C - +85 °C
Min.bending radius	38 mm



PVC/PE sheath
Foamed/solid PE dielectric
Solid copper inner conductor
Bonded aluminium foil
Tinned copper braid outer conductor



Attenuation

Frequency(MHz)	Attenuation (dB/100 m)	Max. Attenuation(dB/100ft)
30	3.5	1.1
50	4.5	1.4
150	7.9	2.4
220	9.6	2.9
450	13.8	4.2
900	19.9	6.1
1500	26.0	7.9
1800	28.7	8.7
2000	30.3	9.2
2500	34.2	10.4
3000	37.5	11.4
5800	54.2	16.5