

RG Type Low Loss Coaxial Cables


RG 8 LLA

Construction


Inner conductor	Plain copper	19 x 0.28 mm
Dielectric	Foam PE	$\Phi 3.90 \pm 0.15$ mm
Outer conductor (shield 1)	Aluminium + polyester tape	
Shield coverage		100%
Outer conductor (shield 2)	Tinned copper	128 x 0.10 mm
Shield coverage		80%
Sheath	PVC or LSZH	$\Phi 6.10 \pm 0.10$ mm

Electrical & Mechanical Characteristics

Impedance	50 \pm 3 Ohm
Nominal capacitance	80 pF/m
Velocity of propagation	80%
Insulation resistance	>5000 Mohm.Km
Inner conductor resistance	15.5 Ohm/Km
Outer conductor resistance	19 Ohm/Km
Operating temperature range	-30 °C - +70 °C
Copper weight	20.8 Kg/Km
Cable weight (approx.)	48.1 Kg/Km
Screening effectiveness	>80 dB



PVC or LSZH sheath
 AL+polyester +ALTape
 Plain copper inner conductor
 Foamed PE dielectric
 Tinned copper outer conductor



Attenuation

Frequency(MHz)	Attenuation (dB/100 m)	Attenuation (dB/100ft)
50	7.3	2.23
100	9.8	2.99
400	19.7	6.01
600	24.9	7.59
860	30.1	9.18
1000	32.9	10.03
1750	45.8	13.96
2400	55.8	17.01

Return Loss

30-300 MHz	>26dB
300-600 MHz	>25dB
600-900 MHz	>23dB

