



Product Service

CERTIFICATE

No. B 098200 0030 Rev. 00

Model(s): FTX300 1RZ1MAZ1-R (N2XRH),
FTX400 1RZ1MZ1-R (N2XRH)

Parameters:

Rated voltage:	600/1000V
Conductors:	Plain or tinned copper wires
Insulation:	XLPE, GP8
Bedding:	LSZH
Armour:	
FTX300 1RZ1MAZ1-R (N2XRH):	armoured with aluminium wire
FTX400 1RZ1MZ1-R (N2XRH):	armoured with galvanized steel wire
Sheath:	LSZH, LTS 1
Sizes:	
FTX300 1RZ1MAZ1-R (N2XRH):	1C x 50mm ² to 1C x 1000mm ²
FTX400 1RZ1MZ1-R (N2XRH):	2C x 1.5mm ² to 4C x 400mm ² , 5C x 1.5mm ² to 5C x 70mm ² , 7C x 1.5mm ² to 37C x 4mm ²

Tested according to: BS 6724:2016

Production Facility(ies): 096882

TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD
 ZERTIFIKAT ◆ CERTIFICATE ◆ 認證證書 ◆ CERTIFICADO ◆ CERTIFICAT