

## FIREROL Medium Wall Single Core Unsheathed & Fire Resistant 0.6/1 kV or 1.8/3 kV EN 50264-3-1 (FRL-MW-1SU-PH15/30/FRL-MW-3SU-PH15/30)



A. Conductor B. Insulation

### Application

- Used as power and control cable for protected installations inside and outside of rail and transport vehicles, where handling and installation cost are an important factor.
- Used in control, auxiliary and main circuit wiring such as cable harnesses, switchboards and control panels, driver desks etc.

### Construction

#### Conductor

Flexible tinned annealed copper wires, stranded as per HD 383 (IEC 60228) class 5

#### Insulation

Mica tape+LSZH elastomeric compound as defined in EN 50264-1 (EI 106 to EI 109)

### Electrical & Mechanical Properties

Nominal Voltage

0.6/1 kV or 1.8/3 kV

Max. Conductor Temperature

90 °C ( fixed installation )

Min. Permissible Ambient Temperature

-25 °C/-40 °C ( fixed installation )

Bending Radius

Fixed installation:  
10 x Overall Diameter (D<12mm);  
12 x Overall Diameter (D>12mm)  
Flexible installation:  
20 x Overall Diameter (D<12mm);  
25 x Overall Diameter (D>12mm)

### Chemical & Environmental Properties

EN 60684-2

No fluorine

EN 50305; EN 60811-2-1

Resistance to mineral oil & fuel oil, acid & alkali

EN 50305

Resistance to ozone

### Fire Performance for Rolling Stock Application

EN 50306-2

Hazard levels HL1, HL2/HL3, HL4

DIN 5510-2

Protection level 1/2/3/4

BS 6853

Interior use 1a, 1b, II; Exterior use 1a, 1b, II

NF F 16-101

F0

### Fire Performance in General

EN 50265-2-1; IEC 60332-1-2; NF C 32-070 2.1 (C2)

Vertical flame propagation for a single insulated wire or cable

EN 50266-2-4 + EN 50305; IEC 60332-3-24;

Vertical flame spread of vertically mounted bunched wires or cables

NF C 32-070 2.2 (C1); VDE 0472 Teil 804

EN 50268-2; IEC 61034-2; NF C 32-073 ;

Low Smoke Emission

NF C 20-902; NF F 16 101; VDE 0472 Teil 816

Halogen Free

EN 50267-2-1; IEC 60754-1; NF C 32-074;

NF C 20-454; VDE 0472 Teil 815

Low Corrosivity (Acidity & Conductivity)

EN 50267-2-2/3; IEC 60754-2; NF C 32-074;

NF C 20-453; VDE 0472 Teil 813

EN 50305; NF X 70-100; NF F 63 808; TM1-04; BS6853

Low Toxicity

NF F 63 808; BS6853; NF F 16 101

Smoke Index

EN50200: 2000

Resistance to fire of unprotected small cable for use in emergency circuits 4 classifications are defined: PH 15,30,60, or 90 mins;

IEC60331-21

The circuit integrity test under fire of cables rated 0.6/1.0kV and below

**FRL-MW-1SU-PH15/30 0.6/1 kV**

Nominal Cross-Sectional Area	Conductor Diameter (a)	Min. Mean Thickness of Insulation	Overall Diameter		Weight	Max. Conductor Resistance	Min. Insulation Resistance	
			Min.	Max.			20 °C	90 °C
mm <sup>2</sup>	mm	mm	mm	mm	kg/km	Ω/km	MΩ x km	MΩ x km
1.0	1.25	0.6	2.6	3.1	15	20	11.4	0.114
1.5	1.5	0.7	3.0	3.6	24	13.7	11.0	0.110
2.5	1.95	0.7	3.4	4.1	36	8.21	9.1	0.091
4	2.5	0.7	4.0	4.7	54	5.09	7.5	0.075
6	3.0	0.7	4.4	5.3	76	3.39	6.5	0.065
10	3.9	0.7	5.3	6.2	121	1.95	5.2	0.052
16	5.0	0.7	6.3	7.5	184	1.24	4.2	0.042
25	6.4	0.9	8.0	9.4	289	0.795	4.1	0.041
35	7.7	0.9	9.2	10.9	395	0.565	3.5	0.035
50	9.2	1.0	10.8	12.7	563	0.393	3.3	0.033
70	11.0	1.1	12.7	14.9	796	0.277	3.0	0.030
95	12.5	1.1	14.1	16.6	1032	0.210	2.7	0.027
120	14.2	1.2	15.9	18.7	1318	0.164	2.7	0.027
150	15.8	1.4	17.8	20.9	1650	0.132	2.7	0.027
185	17.5	1.6	19.8	23.2	2018	0.108	2.6	0.026
240	20.1	1.7	22.4	26.3	2649	0.0817	2.6	0.026
300	22.5	1.8	24.8	29.1	3291	0.0654	2.4	0.024
400	25.8	2.0	28.3	33.2	3850	0.0495	2.4	0.024

**FRL-MW-3SU-PH15/30 1.8/3 kV**

Nominal Cross-Sectional Area	Conductor Diameter (a)	Min. Mean Thickness of Insulation	Overall Diameter		Weight	Max. Conductor Resistance	Min. Insulation Resistance	
			Min.	Max.			20 °C	90 °C
mm <sup>2</sup>	mm	mm	mm	mm	kg/km	Ω/km	MΩ x km	MΩ x km
1.5	1.5	2.0	5.5	6.5	56	13.7	21.0	0.210
2.5	1.95	2.0	5.9	7.0	71	8.21	18.0	0.180
4	2.5	2.0	6.4	7.6	90	5.09	15.5	0.155
6	3.0	2.0	6.9	8.1	114	3.39	13.7	0.137
10	3.9	2.0	7.7	9.1	165	1.95	11.5	0.115
16	5.0	2.0	8.8	10.3	235	1.24	9.5	0.095
25	6.4	2.0	10.1	11.9	320	0.795	7.9	0.079
35	7.7	2.0	11.3	13.3	440	0.565	6.8	0.068
50	9.2	2.0	12.7	14.9	610	0.393	5.9	0.059
70	11.0	2.0	14.4	16.9	850	0.277	5.0	0.050
95	12.5	2.2	16.2	19.0	1110	0.210	4.5	0.045
120	14.2	2.2	17.8	20.9	1400	0.164	4.0	0.040
150	15.8	2.2	19.3	22.6	1710	0.132	3.7	0.037
185	17.5	2.4	21.1	24.7	2110	0.108	3.4	0.034
240	20.1	2.4	23.9	27.8	2750	0.0817	3.0	0.030
300	22.5	2.4	25.8	30.4	3300	0.0654	2.7	0.027
400	25.8	2.6	29.4	34.5	3900	0.0495	2.4	0.024

(a)= For information, indicative only

